

BWS-EXCELL GW 68 INDICATOR



Description

- IP 68: mist-proof, waterproof and dustproof
- Extra-large and wide LCD display (175 x 70mm) 6 digits with 55mm height
- LCD display with COOL WHITE LED backlight
- RS-232+RTC(Real Time Clock) interface
- Up to 1/15,000 display resolution
- Unit switch key for Kilogram (kg) and pound (lb), etc.
- Full range tare, Pre-tare, Auto zero tracking, Sampling counting, Gross/Net Indication
- Hold function, Check mode Lo / Hi / OK, Auto average unit weight, Animal scale function
- Low power indication and auto power off
- The Sleeve connecting stand comes standard; the U shape stand is optional

Specification

Operating Temperature: -10°C ~ 40°C (14°F ~ 104°F)

Power Source: AC110V/230V (±10%) or DC 6V / 4Ah rechargeable battery

Dimensions: 238 x 156 x 90mm (W x H x D)

Display: LCD 6 Digits; 55 mm (Height); COOL LIGHT LED backlight

Options

- Wireless for distance 100M available (SPP mode supported)
- Convenient foot switch for Zero, or Tare, or Print
- RS-485 data-transfer interface
- U shape stand

BYTRONICS COMPUTERS LTD. T/A BYTRONICS WEIGH SCALES

P.O Box 60434-00200 Nairobi Kenya **Website:** www.bytronics.co.ke **E-mail:** bws@bytronics.co.ke

Tel: 254725517852/+733756960/+20388223